

### C-200T Direct Driven Units

Driven Type:	Vehicle Engine Driven Units
Installation:	Split Front Mounted
Compressor	DY5H11 108cc/r
Controller	Digital, In Cab
Application:	2~10m <sup>3</sup>

A cooling system designed for the transportation of fresh or frozen goods in small van with container volume of 2~10m<sup>3</sup>.

- Roof mounted unit and slim evaporator design
- Strong refrigerating and cooling fast
- High-strength plastic enclosure and elegant appearance
- Compact structure, small size, light weight and fuel savings
- Quick installation, simple maintenance and low maintenance cost
- Apply to all kinds of small refrigerated vans

### Specification

Model		C-200T
Temperature Range In Container		-5°C ~ +30°C / -23°F ~ +86°F
Cooling Capacity	0°C    +32°F	1700W / 1462Kcal/h / 5800BTU
Driven Model		Direct Vehicle Engine Driven
Voltage DC (V)		12V/24V
Refrigerant		R134a
Refrigerant Charge		0.8Kg ~ 0.9Kg
Box Temperature Adjustment		Electronic digital display
Safety Protect		High and low pressure switch
Defrosting		Defrosting and heating optional
Compressor	Model	DY5H11
	Displacement	108cc/r
Condenser	Coil	Aluminum micro-channel parallel flow coils
	Fan	1 Axial Fan
	Dimensions&Weight	700×700×190 mm & 15.6 kg
Evaporator	Coil	Aluminum foil with internal ridge copper tube
	Fan	1Axial Fans
	Dimensions&Weight	610×550×175 mm & 11.8 kg
Box Volume (m <sup>3</sup> )	0°C	10m <sup>3</sup>
Optional Function		Heating, Electric standby system AC 220V/380V, CPR Valve

## Application

